

F

E

D

C

B

A

RoHS
Compliant

SYMBOL

REVISION

APPROVAL

DATE

29.50(DIM:A)

25.00(DIM:B)

4.00

0.60

3.00

0.60

2.50

2.37

4.20

2.48

0.9

No. of Pins	Dimension	
	DIM.B	DIM.A
03	5.00	9.50
04	7.50	12.00
05	10.00	14.50
06	12.50	17.00
07	15.00	19.50
08	17.50	22.00
09	20.00	24.50
10	22.50	27.00
11	25.00	29.50

备注：

1. 材质

塑胶材质：NYLON 9T(UL94V-0)

五金端子：黄铜，镍/锡底，GOLD.

2. 产品规格

额定电流：5A/P

瞬时电流：7A

接触电阻：30mΩ MAX

绝缘电阻：100MΩ MIN

耐电压：500V

工作温度：-40 ~105

3. 所用材质符合ROHS要求。

25.00(DIM:B)

2.50

Ø1.10

Recommended P.C.B Layout

Layout Tolerance= +0.05mm

东莞市信音电子科技有限公司

DONGGUAN XINYIN ELECTRONIC TECHNOLOGY CO.,LTD.

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME

CONNECTOR

DRAWING

M.M.Zhang

DWG.No.

PART NO.

SYCBM01R1A-0.9 系列

CHECK

X.Chen

REV.

A1

UNIT :
mmTOLERANCE
OTHERWISEUP TO 5
ABOVE 5 ~30
ABOVE 30
ANGLE±0.2
±0.3
±0.5
±3°ANGLE
0°±3°

APPROVAL

SCALE

2:1

DATE

PAGE

01-07-2016

1 OF 1

F

E

D

C

B

A